NSN 5930-01-302-4334

Hazardous Locations/environmental Protection:

Push Switch - Page 1 of 2

Explosion proof and humidity resistant

Body Style:Panel mounted



View Online at https://aerobasegroup.com/nsn/5930-01-302-4334

Overall Length:
4.814 inches
Overall Height:
0.750 inches
Overall Width:
0.750 inches
Body Width:
0.750 inches
Body Height:
0.750 inches
Case Material:
Metal
Actuator Length:
0.625 inches
Actuator Style:
Rectangular
Actuator Height:
0.120 inches
Actuator Width:
0.625 inches
Actuator Color:
Black and black single actuator
Illuminated Actuator Color:
Black and black single actuator
Actuator Inscription:
Open close single actuator
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
Mounting Surface To Terminal End Distance:
3.535 inches
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Features Provided:
Horizontal split lens
Nonpile-up Contact Arrangement:
$3 \ \mathrm{pole}, \ \mathrm{double} \ \mathrm{throw}, \ \mathrm{both} \ \mathrm{positions} \ \mathrm{maintained} \ \mathrm{single} \ \mathrm{switch} \ \mathrm{unit}$

NSN 5930-01-302-4334

Push Switch - Page 2 of 2



Contact Load Current Rating At Maximum Rated Voltage:

7.500 amperes resistive dc and 5.000 amperes inductive dc and 1.000 amperes lamp dc and 7.500 amperes resistive ac and 5.000 amperes inductive ac and 1.000 amperes lamp ac

Special Features:

Dim/test control module provided; illuminated actuator inscription is green and amber

Precious Material And Location:

Contacts silver

Terminal Type And Quantity:

1 socket, integrated wire termination

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0