## NSN 5930-01-302-5987

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-302-5987

#### **Body Style:**

Panel mount

#### Hazardous Locations/environmental Protection:

Driptight and dustproof

**Overall Length:** 

0.970 inches

#### **Overall Height:**

1.900 inches

#### **Overall Width:**

0.970 inches

- **Body Length:**
- 0.680 inches

Body Width:

#### 0.680 inches

**Body Height:** 

## 1.300 inches

Case Material:

Metal

Actuator Length:

0.610 inches

#### **Actuator Style:**

Rectangular

#### **Actuator Height:**

0.450 inches

## Actuator Width:

0.610 inches

Actuator Color:

Black single actuator and white single actuator

#### Illuminated Actuator Color:

Black single actuator and white single actuator

#### **Actuator Inscription:**

Double asterisks (symbol), 0 single actuator

#### Maximum Voltage Rating In Volts:

28.0 dc

#### **End Application:**

Indicator group an/spa-25g

Inclosure Type:

Fully enclosed

#### **Mounting Method:**

Panel

## **Features Provided:**

Actuator seal and rfi shielding

# NSN 5930-01-302-5987

Push Switch - Page 2 of 2



## Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

#### Contact Load Current Rating At Maximum Rated Voltage:

1.000 amperes resistive dc and 0.500 amperes inductive dc

#### **Special Features:**

Actuator inscription is white and is sunlight readable

## Precious Material And Location:

Contact surfaces gold and contacts silver

#### Unable To Decode:

Unable to decode and unable to decode

#### Terminal Type And Quantity:

9 printed circuit

Shelf Life:

N/a

#### Unit Of Measure:

---

## Demilitarization:

No

#### Fiig:

A053a0