NSN 5930-01-302-5989Push Switch - Page 1 of 2



rush Switch - rage 1 of 2	Group
View Online at https://aerobasegroup.com/nsn/5930-01-302-5989	
Body Style:	
Panel mount	
Hazardous Locations/environmental Protection:	
Driptight and dustproof	
Overall Length:	
0.970 inches	
Overall Height:	
1.900 inches	
Overall Width:	
0.970 inches	
Body Length:	
0.680 inches	
Body Width:	
0.680 inches	
Body Height:	
1.300 inches	
Case Material:	
Metal	
Actuator Length:	
0.610 inches	
Actuator Style:	
Rectangular	
Actuator Height:	
0.450 inches	
Actuator Width:	
0.610 inches	
Actuator Color:	
Black single actuator	
Illuminated Actuator Color:	
Black single actuator	
Actuator Inscription:	
Pd origin to pd single actuator	
Maximum Voltage Rating In Volts:	
28.0 dc	
End Application:	

Inclosure Type:

Indicator group an/spa-25g

Fully enclosed

Mounting Method:

Panel

Features Provided:

Actuator seal and rfi shielding

NSN 5930-01-302-5989

Push Switch - Page 2 of 2



Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

1.000 amperes resistive dc and 0.500 amperes inductive dc

Special Features:

Actuator inscription is white and is sunlight readable

Precious Material And Location:

Contact surfaces gold and contacts silver

Unable To Decode:

Unable to decode and unable to decode

Terminal Type And Quantity:

9 printed circuit

•

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0