NSN 5930-01-302-5990

Push Switch - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5930-01-302-5990



Body Style:

Panel mount

Hazardous Locations/environmental Protection:

Driptight and dustproof

Overall Length:

0.970 inches

Overall Height:

1.900 inches

Overall Width:

0.970 inches

Body Length:

0.680 inches

Body Width:

0.680 inches

_

Body Height:

1.300 inches

Case Material:

Metal

Actuator Length:

0.610 inches

Actuator Style:

Rectangular

Actuator Height:

0.450 inches

Actuator Width:

0.610 inches

Actuator Color:

Black single actuator

Illuminated Actuator Color:

Black single actuator

Actuator Inscription:

Offset single actuator

Maximum Voltage Rating In Volts:

28.0 dc

End Application:

Indicator group an/spa-25g

Inclosure Type:

Fully enclosed

Mounting Method:

Panel

Features Provided:

Actuator seal and rfi shielding

NSN 5930-01-302-5990

Push Switch - Page 2 of 2



Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

1.000 amperes resistive dc and 0.500 amperes inductive dc

Special Features:

Actuator inscription is white and is sunlight readable

Precious Material And Location:

Contact surfaces gold and contacts silver

Unable To Decode:

Unable to decode and unable to decode

Terminal Type And Quantity:

9 printed circuit

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0