# NSN 5930-01-302-5991

Push Switch - Page 1 of 2

**Body Style:** 



View Online at https://aerobasegroup.com/nsn/5930-01-302-5991

Panel mount
Hazardous Locations/environmental Protection:
Dustproof and driptight
Overall Length:
0.970 inches
Overall Height:
1.900 inches
Overall Width:
0.970 inches
Body Length:
0.680 inches
Body Width:
0.680 inches
Body Height:
1.300 inches
Case Material:
Metal
Actuator Length:
0.610 inches
Actuator Style:
Rectangular
Actuator Height:
0.450 inches
Actuator Width:
0.610 inches
Actuator Color:
Black single actuator and white single actuator
Illuminated Actuator Color:
Black single actuator and white single actuator
Actuator Inscription:
Plot, 1 single actuator
Maximum Voltage Rating In Volts:
28.0 dc
End Application:
Indicator group an/spa-25g
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Features Provided:
Actuator seal and rfi shielding

## NSN 5930-01-302-5991

Push Switch - Page 2 of 2



### **Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

### **Contact Load Current Rating At Maximum Rated Voltage:**

1.000 amperes resistive dc and 0.500 amperes inductive dc

### **Special Features:**

Actuator inscription is white and is sunlight readable

### **Precious Material And Location:**

Contact surfaces gold and contacts silver

#### **Unable To Decode:**

Unable to decode and unable to decode

### **Terminal Type And Quantity:**

9 printed circuit

Shelf Life:

Onch Enc

N/a

**Unit Of Measure:** 

--

**Demilitarization:** 

No

Fiig:

A053a0