# NSN 5930-01-302-7008

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-302-7008

### **Body Style:**

Panel mount

#### Hazardous Locations/environmental Protection:

Waterproof

# **Overall Length:**

1.100 inches

#### **Overall Height:**

3.250 inches

#### **Overall Width:**

1.100 inches

- **Body Length:**
- 0.850 inches

Body Width:

### 0.850 inches

**Body Height:** 

# 2.600 inches

Actuator Style:

Rectangular

#### Actuator Height:

0.350 inches

# Actuator Color:

White single actuator

#### Illuminated Actuator Color:

Red single actuator

#### **Actuator Inscription:**

Over temp single actuator

#### Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

#### Inclosure Type:

Fully enclosed

#### **Mounting Method:**

Panel

#### **Features Provided:**

Rfi shielding

#### **Nonpile-up Contact Arrangement:**

4 pole, double throw, one position momentary single switch unit

# Contact Load Current Rating At Maximum Rated Voltage:

2.000 amperes resistive dc and 1.000 amperes inductive dc and 0.750 amperes lamp dc and 2.000 amperes resistive ac and 1.000 amperes inductive ac and 0.750 amperes lamp ac

inductive ac and 0.750 amperes tamp

# Terminal Type And Quantity:

1 connector, receptacle

#### Shelf Life:

# NSN 5930-01-302-7008

Push Switch - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A053a0

