## NSN 5930-01-302-8989

Toggle Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-302-8989

| Thread Class:  |
|--|
| 2a   |
| Body Style:  |
| Bushing mount  |
| Bushing Length:  |
| 0.350 inches   |
| Body Length:   |
| 0.500 inches   |
| Body Width:  |
| 0.450 inches   |
| Body Height:   |
| 0.410 inches   |
| Actuator Style:  |
| Rectangular  |
| Actuator Height:   |
| 0.450 inches   |
| Actuator Width:  |
| 0.100 inches   |
| Actuator Position-action Relationship:   |
| Up position momentary and down position momentary and center position maintained |
| Maximum Voltage Rating In Volts:   |
| 250.0 ac and 28.0 dc   |
| Inclosure Type:  |
| Fully enclosed   |
| Mounting Method:   |
| Threaded bushing   |
| Thready Qty Per Inch (tpi):  |
| 40   |
| Thread Size:   |
| 0.250 inches   |
| Nonpile-up Contact Arrangement:  |
| 2 pole, double throw, two positions momentary single switch unit                 |
| Contact Load Current Rating At Maximum Rated Voltage:                            |
| 5.000 amperes resistive dc and 2.000 amperes resistive ac                        |
| Special Features:  |
| Terminal sealing; antirotation feature   |
| Precious Material And Location:  |
| Contact and terminal surfaces silver   |
| Thread Series Designator:  |
| Uns  |
| Terminal Type And Quantity:  |
| 6 tab, solder lug  |

## **NSN 5930-01-302-8989** Toggle Switch - Page 2 of 2



| _  |   |   |    |    |    |
|----|---|---|----|----|----|
| ٠. | n | _ | I+ | 18 | e: |
|    |   |   |    |    |    |

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A053a0