Pressure-thermostatic Switch - Page 1 of 2



Pressure-thermostatic Switch - Page 1 of 2
View Online at https://aerobasegroup.com/nsn/5930-01-303-0695
Hazardous Locations/environmental Protection:
Splashproof
Overall Width:
3.750 inches
Body Length:
4.250 inches
Body Height:
4.500 inches
Capillary Tube Length:
48.0 inches
Bulb Length:
2.500 inches
Bulb Diameter:
0.500 inches
Pressure Switch Type:
Gage
Tempurature Sensing Element Type:
Capillary tube-bulb
Operating Tempurature Rating:
-138.0 degrees fahrenheit
Mounting Method:
Bracket and slot
Features Provided:
Electrical access port
Proof Pressure:
230.00 pounds per square inch
Thread Size:
0.125 inches single pressure connection
Mounting Facility Pattern:
Isosceles triangle
Nonpile-up Contact Arrangement:
2 pole, double throw, both positions maintained
Terminal Type:
Tab w/screw
Contact Load Current Rating:
7.5 amperes motor load second voltage
Contact Adjustability:
Actuation point adjustable
Contact Adjustment Range:
+165.00/+215.00 actuation point degrees fahrenheit or +10.00/+70.00 actuation point pounds per square inch
Contact Adjustment Type:

External actuation point screw



**Contact Voltage Rating In Volts:** 6.0 dc at sea level third voltage Media For Which Designed: Gas or liquid Style Designator: Rectangular w/mounting lugs **Thread Series Designator:** Npt single pressure connection Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A048b0