

View Online at <https://aerobasegroup.com/nsn/5930-01-303-0695>

Hazardous Locations/environmental Protection:

Splashproof

Overall Width:

3.750 inches

Body Length:

4.250 inches

Body Height:

4.500 inches

Capillary Tube Length:

48.0 inches

Bulb Length:

2.500 inches

Bulb Diameter:

0.500 inches

Pressure Switch Type:

Gage

Temperature Sensing Element Type:

Capillary tube-bulb

Operating Temperature Rating:

-138.0 degrees fahrenheit

Mounting Method:

Bracket and slot

Features Provided:

Electrical access port

Proof Pressure:

230.00 pounds per square inch

Thread Size:

0.125 inches single pressure connection

Mounting Facility Pattern:

Isosceles triangle

Nonpile-up Contact Arrangement:

2 pole, double throw, both positions maintained

Terminal Type:

Tab w/screw

Contact Load Current Rating:

7.5 amperes motor load second voltage

Contact Adjustability:

Actuation point adjustable

Contact Adjustment Range:

+165.00/+215.00 actuation point degrees fahrenheit or +10.00/+70.00 actuation point pounds per square inch

Contact Adjustment Type:

External actuation point screw

Contact Voltage Rating In Volts:

6.0 dc at sea level third voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular w/mounting lugs

Thread Series Designator:

Npt single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0