

View Online at <https://aerobasegroup.com/nsn/5930-01-303-2916>

Thread Class:

2a

Body Style:

Bushing mounted

Hazardous Locations/environmental Protection:

Corrosion resistant and moisture resistant

Body Diameter:

0.560 inches

Bushing Length:

0.593 inches

Body Length:

Between 0.585 inches and 0.647 inches

Actuator Style:

Round, dual

Actuator Diameter:

1.125 inches

Actuator Height:

0.541 inches

Actuator Color:

Gray single actuator

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

24

Thread Size:

0.620 inches

Nonpile-up Contact Arrangement:

1 pole, single throw, double make, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

10.000 amperes resistive dc and 5.000 amperes inductive dc and 5.000 amperes lamp dc and 10.000 amperes resistive ac and 5.000 amperes inductive ac and 5.000 amperes lamp ac

Thread Series Designator:

Unef

Terminal Type And Quantity:

2 tab w/screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0