

View Online at <https://aerobasegroup.com/nsn/5930-01-303-6071>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Oiltight

Actuator Style:

Roller plunger

Actuator Free Position Height:

1.840 inches

Actuator Roller Diameter:

0.500 inches

Housing Height:

1.530 inches

Housing Length:

4.150 inches

Housing Width:

1.780 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Length:

2.344 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Width:

1.156 inches

Maximum Voltage Rating In Volts:

600.0 ac and 600.0 dc

Inclosure Type:

Fully enclosed

Nonpile-up Contact Arrangement:

1 two circuit, double break/double make, one position momentary single switch unit

Switch Actuating Force:

72.0 ounces

Actuator Movement:

0.125 pretravel inches and 0.093 overtravel inches and 0.057 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

0.100 amperes resistive dc and 1.200 amperes resistive ac

Terminal Type And Quantity:

4 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0