

View Online at <https://aerobasegroup.com/nsn/5930-01-303-6072>

Thread Class:

2a

Body Style:

Bushing mounted

Bushing Length:

0.625 inches

Body Length:

0.555 inches

Body Width:

0.510 inches

Body Height:

0.500 inches

Actuator Style:

Round

Actuator Diameter:

0.250 inches

Actuator Height:

0.250 inches

Actuator Free Position Height:

0.875 inches

Maximum Voltage Rating In Volts:

28.0 dc

End Application:

5815-01-211-4122 terminal, communications an/ugc-7 (v) 3

Inclosure Type:

Uninclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

Switch Release Force:

64.0 ounces

Criticality Code Justification:

Feat

Switch Actuating Force:

144.0 ounces

Actuator Movement:

0.040 pretravel inches and 0.125 overtravel inches

Contact Load Current Rating At Maximum Rated Voltage:

7.000 amperes resistive dc and 4.000 amperes inductive dc and 4.000 amperes motor dc

Special Features:

Weapon system essential

Thread Series Designator:

Uns

Terminal Type And Quantity:

6 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0