## NSN 5930-01-303-6073

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-303-6073 **Body Style:** Hole mounted **Actuator Style:** Roller plunger **Actuator Free Position Height:** 1.900 inches **Actuator Roller Diameter:** 0.500 inches **Actuator Roller Width:** 0.150 inches **Housing Height:** 1.970 inches **Housing Length:** 3.810 inches **Housing Width:** 1.180 inches **Center To Center Distance Between Housing Mounting Facilities Parallel To Length:** 2.050 inches Center To Center Distance Between Housing Mounting Facilities Parallel To Width: 1.580 inches **Maximum Voltage Rating In Volts:** 240.0 ac **Inclosure Type:** Fully enclosed **Features Provided:** Actuator seal **Nonpile-up Contact Arrangement:** 1 pole, double throw, one position momentary single switch unit **Switch Actuating Force:** 13.5 newtons **Actuator Movement:** Between 0.120 pretravel inches and 0.197 overtravel inches and 0.005 differential inches **Contact Load Current Rating At Maximum Rated Voltage:** 10.000 amperes resistive ac and 10.000 amperes inductive ac **Terminal Type And Quantity:** 3 screw Shelf Life: N/a **Unit Of Measure:** 

No

**Demilitarization:** 

## **NSN 5930-01-303-6073** Sensitive Switch - Page 2 of 2



Fiig:

A053a0