

View Online at <https://aerobasegroup.com/nsn/5930-01-303-6073>

Body Style:

Hole mounted

Actuator Style:

Roller plunger

Actuator Free Position Height:

1.900 inches

Actuator Roller Diameter:

0.500 inches

Actuator Roller Width:

0.150 inches

Housing Height:

1.970 inches

Housing Length:

3.810 inches

Housing Width:

1.180 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Length:

2.050 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Width:

1.580 inches

Maximum Voltage Rating In Volts:

240.0 ac

Inclosure Type:

Fully enclosed

Features Provided:

Actuator seal

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Actuating Force:

13.5 newtons

Actuator Movement:

Between 0.120 pretravel inches and 0.197 overtravel inches and 0.005 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

10.000 amperes resistive ac and 10.000 amperes inductive ac

Terminal Type And Quantity:

3 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0