NSN 5930-01-303-6848

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-303-6848

| Body Style: |
|--|
| Panel mount |
| Hazardous Locations/environmental Protection: |
| Dustproof and moisture proof |
| Overall Length: |
| 1.330 inches |
| Overall Height: |
| 0.623 inches |
| Overall Width: |
| 0.623 inches |
| Body Diameter: |
| 0.562 inches |
| Body Length: |
| 0.900 inches |
| Case Material: |
| Metal |
| Actuator Diameter: |
| 0.370 inches |
| Actuator Height: |
| 0.250 inches |
| Actuator Color: |
| Red single actuator |
| Maximum Voltage Rating In Volts: |
| 115.0 ac and 28.0 dc |
| Inclosure Type: |
| Fully enclosed |
| Mounting Method: |
| Panel |
| Features Provided: |
| Actuator seal |
| Nonpile-up Contact Arrangement: |
| 1 pole, single throw, normally open, double make, momentary action single switch unit |
| Contact Load Current Rating At Maximum Rated Voltage: |
| 10.000 amperes resistive dc and 5.000 amperes inductive dc and 3.000 amperes lamp dc and 10.000 amperes resistive ac and 5.000 |
| amperes inductive ac and 3.000 amperes lamp ac |
| Terminal Type And Quantity: |
| 2 tab, solder lug |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| - |
| Demilitarization: |

No

NSN 5930-01-303-6848

Push Switch - Page 2 of 2



Fiig:

A053a0