

View Online at <https://aerobasegroup.com/nsn/5930-01-303-8788>

Hazardous Locations/environmental Protection:

Explosion proof

Overall Length:

4.875 inches

Overall Height:

7.875 inches

Overall Width:

3.250 inches

Unthreaded Mounting Hole Diameter:

0.281 inches

Longest Horizontal Distance Between Mounting Centers:

4.375 inches

Shortest Horizontal Distance Between Mounting Centers:

2.187 inches

Longest Vertical Distance Between Mounting Centers:

4.000 inches

Pressure Switch Type:

Differential

Mounting Method:

Flange and unthreaded hole

Features Provided:

Electrical access port

Contact Action Stimulus:

Increase

Proof Pressure:

2000.00 pounds per square inch

Mounting Facility Pattern:

Isosceles triangle

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Tab w/screw

Contact Load Current Rating:

0.4 amperes resistive load third voltage

Contact Adjustability:

Actuation point adjustable

Contact Adjustment Range:

+2.50/+30.00 actuation point pounds per square inch gage

Contact Adjustment Type:

Internal actuation point hex nut

Contact Voltage Rating In Volts:

250.0 ac at sea level second voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0