

View Online at <https://aerobasegroup.com/nsn/5930-01-304-1925>

**Body Style:**

Bushing mounted

**Overall Length:**

0.900 inches

**Overall Height:**

0.562 inches

**Overall Width:**

0.562 inches

**Body Diameter:**

0.380 inches

**Bushing Length:**

0.260 inches

**Body Length:**

0.100 inches

**Actuator Diameter:**

0.190 inches

**Actuator Height:**

0.125 inches

**Actuator Color:**

Black single actuator

**Maximum Voltage Rating In Volts:**

28.0 dc

**End Application:**

Receiving set, telemetric data an/skr-4a

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.469 inches

**Nonpile-up Contact Arrangement:**

1 pole, single throw, normally open, double make, momentary action single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

5.000 amperes resistive dc and 3.000 amperes inductive dc and 1.000 amperes lamp dc and 3.000 amperes motor dc

**Test Data Document:**

81349-mil-prf-8805 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

2 tab, solder lug

**Specification Data:**

81349-mil-prf-8805/110 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0

**Mil-std (military Standard):**

Mil-prf-8805 spec.