

View Online at <https://aerobasegroup.com/nsn/5930-01-304-1925>

Body Style:

Bushing mounted

Overall Length:

0.900 inches

Overall Height:

0.562 inches

Overall Width:

0.562 inches

Body Diameter:

0.380 inches

Bushing Length:

0.260 inches

Body Length:

0.100 inches

Actuator Diameter:

0.190 inches

Actuator Height:

0.125 inches

Actuator Color:

Black single actuator

Maximum Voltage Rating In Volts:

28.0 dc

End Application:

Receiving set, telemetric data an/skr-4a

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, double make, momentary action single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 3.000 amperes inductive dc and 1.000 amperes lamp dc and 3.000 amperes motor dc

Test Data Document:

81349-mil-prf-8805 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Uns

Terminal Type And Quantity:

2 tab, solder lug

Specification Data:

81349-mil-prf-8805/110 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0

Mil-std (military Standard):

Mil-prf-8805 spec.