## NSN 5930-01-304-3309

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-304-3309		
Thread Class:		
2b single mounting facility		
Hazardous Locations/environmental Protection:		
Shock resistant and vibration resistant		
Overall Length:		
2.874 inches		
Overall Height:		
2.500 inches		
Overall Width:		
3.000 inches		
Individual Section Quantity:		
4		
Switch Contact Basic Design:		
Nonpile-up nonsymmetrical		
Mounting Facility Circle Radius:		
1.156 inches single mounting facility		
Mounting Method:		
Bracket single mounting facility and threaded hole single mounting facility		
Thready Qty Per Inch (tpi):		
24 single mounting facility		
Thread Size:		
0.190 inches single mounting facility		
Contact Voltage Rating In Volts:		
120.0 dc at sea level		
Mounting Facility Pattern:		
Four position circular single mounting facility		
Switch Actuator Indexing Position Quantity:		
3 single actuator		
Terminal Type:		
Tab w/screw		
Contact Switching Action:		
Breaks before makes each section periphery		
Switch Actuator Positioning Increment:		
90.0 degrees single actuator		
Switch Actuator Stop Device Type:		
Fixed stop single actuator		
Contact Load Current Rating:		
10.0 amperes resistive load dc at sea level		
Style Designator:		
Tap, circuit selector		

**Thread Series Designator:** Unc single mounting facility

## NSN 5930-01-304-3309

Rotary Switch - Page 2 of 2



	Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A052b0