NSN 5930-01-304-3310

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-304-3310

View Online at https://aerobasegroup.com/nsn/5930-01-304-3310
Thread Class:
2a single mounting facility
Hazardous Locations/environmental Protection:
Corrosion resistant
Overall Length:
5.340 inches
Overall Height:
2.910 inches
Overall Width:
2.810 inches
Individual Section Quantity:
2
Knob Manufacturer Code:
82121
Knob Manufacturer Part Number:
02000-10
Longest Horizontal Distance Between Mounting Centers:
2.000 inches single mounting facility
Shortest Horizontal Distance Between Mounting Centers:
1.000 inches single mounting facility
Longest Vertical Distance Between Mounting Centers:
2.180 inches single mounting facility
Switch Contact Basic Design:
Nonpile-up nonsymmetrical
Mounting Method:
Bracket single mounting facility and threaded hole single mounting facility
Features Provided:
Actuator knob
Thread Size:
0.190 inches single mounting facility
Contact Voltage Rating In Volts:
500.0 highest ac voltage rating at sea level
Mounting Facility Pattern:
Isosceles triangle single mounting facility
Switch Actuator Indexing Position Quantity:
8 single actuator
Terminal Type:
Tab w/screw
Contact Switching Action:

45.0 degrees single actuator

Breaks before makes each section periphery

Switch Actuator Positioning Increment:

NSN 5930-01-304-3310Rotary Switch - Page 2 of 2

Fiig: A052b0



Switch Actuator Stop Device Type:
Adjustable stop single actuator
Contact Load Current Rating:
5.0 amperes resistive load highest ac voltage rating at sea level
Precious Material And Location:
Rotor and stator surfaces silver
Precious Material:
Silver
Style Designator:
Tap, circuit selector
Thread Series Designator:
Unf single mounting facility
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No