## NSN 5930-01-304-5857

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-304-5857

Body Style:
Hole mounted
Hazardous Locations/environmental Protection:
Humidity resistant
Overall Length:
3.386 inches
Overall Height:
2.981 inches
Actuator Style:
Roller plunger
Actuator Roller Diameter:
0.500 inches
Actuator Roller Width:
0.189 inches
Housing Height:
1.752 inches
Housing Width:
1.000 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Length:
1.000 inches
Maximum Voltage Rating In Volts:
480.0 ac and 250.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary single switch unit
Switch Release Force:
114.0 grams
Switch Actuating Force:
Between 250.0 grams and 350.0 grams
Actuator Movement:
Between 0.020 pretravel inches and 0.142 overtravel inches and 0.002 differential inches
Contact Load Current Rating At Maximum Rated Voltage:
250.0 milliamperes resistive dc and 30.0 milliamperes inductive dc and 250.0 milliamperes lamp dc and 30.0 milliamperes motor dc and
10.000 amperes resistive ac and 6.000 amperes inductive ac and 1.500 amperes lamp ac and 1.500 amperes motor ac
Terminal Type And Quantity:
3 screw
Shelf Life:
N/a
Unit Of Measure:

--

## NSN 5930-01-304-5857

Sensitive Switch - Page 2 of 2



_		••	• •				
וו	em	ш	112	rız	211	n	٠.

No

Fiig:

A053a0