## NSN 5930-01-304-5857

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-304-5857

## **Body Style:**

Hole mounted

## Hazardous Locations/environmental Protection:

Humidity resistant

## **Overall Length:**

3.386 inches

### **Overall Height:**

2.981 inches

#### Actuator Style:

Roller plunger

#### Actuator Roller Diameter:

0.500 inches

### Actuator Roller Width:

0.189 inches

### **Housing Height:**

1.752 inches

### Housing Width:

1.000 inches

## Center To Center Distance Between Housing Mounting Facilities Parallel To Length:

1.000 inches

## Maximum Voltage Rating In Volts:

480.0 ac and 250.0 dc

## Inclosure Type:

Fully enclosed

#### **Mounting Method:**

Unthreaded hole

## Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

## Switch Release Force:

114.0 grams

#### Switch Actuating Force:

Between 250.0 grams and 350.0 grams

#### **Actuator Movement:**

Between 0.020 pretravel inches and 0.142 overtravel inches and 0.002 differential inches

## Contact Load Current Rating At Maximum Rated Voltage:

250.0 milliamperes resistive dc and 30.0 milliamperes inductive dc and 250.0 milliamperes lamp dc and 30.0 milliamperes motor dc and

10.000 amperes resistive ac and 6.000 amperes inductive ac and 1.500 amperes lamp ac and 1.500 amperes motor ac

#### **Terminal Type And Quantity:**

3 screw

## Shelf Life:

N/a

#### Unit Of Measure:

# NSN 5930-01-304-5857

Sensitive Switch - Page 2 of 2

Demilitarization:

No

Fiig:

A053a0

