NSN 5930-01-304-6834



Thermostatic Switch - Page 1 of 2)
View Online at https://aerobasegroup.com/nsn/5930-01-304-6834	
Thread Class:	
2a all threaded stud	
Hazardous Locations/environmental Protection:	
Vibration resistant	
Overall Length:	
1.590 inches	
Body Diameter:	
0.300 inches	
Body Length:	
0.700 inches	
Overall Diameter:	
0.300 inches	
Distance Between Mounting Facility Centers:	
0.700 inches	
Tempurature Sensing Element Type:	
Internal sensor	
Mounting Method:	
Bracket and threaded stud	
Thready Qty Per Inch (tpi):	
40 all threaded stud	
Contact Action Stimulus:	
Increase	
Thread Size:	
0.112 inches all threaded stud	
Mounting Facility Pattern:	
Two position in-line	
Nonpile-up Contact Arrangement:	
1 pole, single throw, normally closed, momentary action	
Terminal Type:	
Wire lead	
Contact Load Current Rating:	
1.0 amperes resistive load second voltage	
Contact Adjustability:	

Actuation point not adjustable

Contact Stimulus Rating:

70.00 actuation point degrees celsius

Contact Voltage Rating In Volts:

120.0 ac at sea level first voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Cylindrical

NSN 5930-01-304-6834

Thermostatic Switch - Page 2 of 2



Ī	hread	Series	Designato	r:

Unc all threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0