NSN 5930-01-304-6835

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-304-6835

Th	read	I C	lass:

2a single threaded stud

Hazardous Locations/environmental Protection:

Corrosion resistant and moisture resistant and vibration resistant

Overall Height:

1.093 inches

Body Height:

0.327 inches

Overall Diameter:

Between 0.623 inches and 0.640 inches

Tempurature Sensing Element Type:

Internal sensor

Operating Tempurature Rating:

Between 62.0 degrees celsius and 100.0 degrees celsius

Mounting Method:

Threaded stud

Features Provided:

Hermetically sealed case

Thready Qty Per Inch (tpi):

32 single threaded stud

Contact Action Stimulus:

Increase

Thread Size:

0.138 inches single threaded stud

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action

Terminal Type:

Tab, solder lug

Contact Load Current Rating:

5.0 amperes resistive load third voltage

Contact Adjustability:

Actuation point not adjustable and deactuation point not adjustable

Contact Stimulus Rating:

179.00 actuation point degrees fahrenheit and 165.00 deactuation point degrees fahrenheit

Contact Voltage Rating In Volts:

30.0 dc at sea level third voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Disc

Thread Series Designator:

Unc single threaded stud

NSN 5930-01-304-6835

Thermostatic Switch - Page 2 of 2



_					
C.	~~	14	I i	ife:	
J.	16			HE.	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0