NSN 5930-01-304-6848

Sensitive Switch - Page 1 of 2

Thread Class:

Body Style:

Bushing mounted

2a



View Online at https://aerobasegroup.com/nsn/5930-01-304-6848

Actuator Length:
Between 1.750 inches and 3.800 inches
Actuator Style:
Adjustable arm
Actuator Diameter:
0.180 inches
Actuator Height:
1.270 inches
Actuator Width:
2.500 inches
Housing Diameter:
1.000 inches
Housing Length:
1.030 inches
Housing Bushing Length:
0.340 inches
Maximum Voltage Rating In Volts:
28.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Threaded bushing
Thready Qty Per Inch (tpi):
32
Thread Size:
0.469 inches
Nonpile-up Contact Arrangement:
2 pole, double throw, one position momentary single switch unit
Switch Actuating Force:
48.0 inch-ounces
Actuator Movement:
12.0 pretravel degrees and 348.0 overtravel degrees
Contact Load Current Rating At Maximum Rated Voltage:
4.000 amperes resistive dc and 3.000 amperes inductive dc and 4.000 amperes motor dc
Thread Series Designator:
Uns
Terminal Type And Quantity:
1 cable w/connector

NSN 5930-01-304-6848

Sensitive Switch - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0