

View Online at <https://aerobasegroup.com/nsn/5930-01-304-6848>

**Thread Class:**

2a

**Body Style:**

Bushing mounted

**Actuator Length:**

Between 1.750 inches and 3.800 inches

**Actuator Style:**

Adjustable arm

**Actuator Diameter:**

0.180 inches

**Actuator Height:**

1.270 inches

**Actuator Width:**

2.500 inches

**Housing Diameter:**

1.000 inches

**Housing Length:**

1.030 inches

**Housing Bushing Length:**

0.340 inches

**Maximum Voltage Rating In Volts:**

28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.469 inches

**Nonpile-up Contact Arrangement:**

2 pole, double throw, one position momentary single switch unit

**Switch Actuating Force:**

48.0 inch-ounces

**Actuator Movement:**

12.0 pretravel degrees and 348.0 overtravel degrees

**Contact Load Current Rating At Maximum Rated Voltage:**

4.000 amperes resistive dc and 3.000 amperes inductive dc and 4.000 amperes motor dc

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

1 cable w/connector

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0