NSN 5930-01-304-6856

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-304-6856
Body Style:
Panel mount
Hazardous Locations/environmental Protection:
Shock resistant
Overall Length:
1.200 inches
Overall Height:
3.320 inches
Overall Width:
0.960 inches
Body Length:
0.660 inches
Body Width:
0.960 inches
Body Height:
3.110 inches
Actuator Length:
Between 1.020 inches and 1.035 inches
Actuator Style:
Rectangular
Actuator Height:
Between 0.164 inches and 0.210 inches
Actuator Width:
Between 0.607 inches and 0.630 inches
Actuator Color:
White single actuator
Illuminated Actuator Color:
White single actuator
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
End Application:
5895-01-269-3572 landing control
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Nonpile-up Contact Arrangement:
2 pole, double throw, both positions maintained single switch unit
Contact Load Current Rating At Maximum Rated Voltage:
5.000 amperes resistive dc and 3.000 amperes inductive dc and 2.400 amperes lamp dc and 5.000 amperes resistive ac and 5.000 amperes
inductive ac and 1.500 amperes lamp ac

Test Data Document:

81349-mil-s-22885 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain

NSN 5930-01-304-6856

Push Switch - Page 2 of 2



Terminal Type Ar	nd Quantity
6 turret and 6 tab,	solder lug

Specification Data:

81349-mil-s-22885/9 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0