NSN 5930-01-304-9105

Pressure Switch - Page 1 of 2

6.0 dc at sea level third voltage



View Online at https://aerobasegroup.com/nsn/5930-01-304-9105

Hazardous Locations/environmental Protection:
Watertight
Overall Length:
5.250 inches
Overall Height:
5.281 inches
Overall Width:
2.281 inches
Body Length:
4.000 inches
Body Height:
3.750 inches
Unthreaded Mounting Hole Diameter:
0.281 inches
Distance Between Mounting Facility Centers:
4.625 inches
Pressure Switch Type:
Gage
Mounting Method:
Flange and unthreaded hole
Features Provided:
Electrical access port and automatic reset
Contact Action Stimulus:
Increase
Proof Pressure:
2000.00 pounds per square inch
Mounting Facility Pattern:
Two position in-line
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary
Terminal Type:
Tab w/screw
Contact Load Current Rating:
30.0 milliamperes resistive load fourth voltage
Contact Adjustability:
Actuation point adjustable
Contact Adjustment Range:
+4.50/+85.00 actuation point pounds per square inch and +3.00/+78.00 deactuation point pounds per square inch
Contact Adjustment Type:
External actuation point screw
Contact Voltage Rating In Volts:

NSN 5930-01-304-9105Pressure Switch - Page 2 of 2



Media For Which Designed:
Gas or liquid
Style Designator:
Rectangular
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A048b0