

View Online at <https://aerobasegroup.com/nsn/5930-01-305-0302>

Thread Class:

2b

Body Style:

Bushing mounted

Hazardous Locations/environmental Protection:

Watertight

Overall Length:

2.355 inches

Body Diameter:

1.015 inches

Bushing Length:

1.030 inches

Body Length:

0.980 inches

Actuator Style:

Round

Actuator Diameter:

0.250 inches

Actuator Height:

0.375 inches

Actuator Free Position Height:

1.375 inches

Maximum Voltage Rating In Volts:

28.0 dc

End Application:

2350-01-219-7577 carrier, personnel

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded hole

Thread Size:

0.625 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, double break/double make, permanent jumper, one position momentary single switch unit

Switch Release Force:

64.0 ounces

Switch Actuating Force:

144.0 ounces

Actuator Movement:

Between 0.040 pretravel inches and 0.250 overtravel inches and 0.020 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

4.000 amperes resistive dc and 2.000 amperes inductive dc and 4.000 amperes motor dc

Thread Series Designator:

Unef

Terminal Type And Quantity:

1 cable w/connector

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0