

View Online at <https://aerobasegroup.com/nsn/5930-01-305-3555>

Mounting Slot Width:

0.187 inches

Capillary Tube Length:

96.0 inches

Bulb Length:

5.750 inches

Bulb Diameter:

0.375 inches

End Application:

Controller/starter used onboard 180 ft wlb coast guard vessels

Temperature Sensing Element Type:

Capillary tube-bulb

Mounting Method:

Slot

Cubic Measure:

5.000 cubic inches

Contact Action Stimulus:

Increase

Nonpile-up Contact Arrangement:

1 pole, single throw, double make, both positions maintained, with contact on arm

Terminal Type:

Screw

Contact Load Current Rating:

3.7 amperes motor load second voltage

Contact Adjustability:

Actuation point adjustable, preset and deactuation point adjustable, preset

Contact Adjustment Range:

+50.00/+90.00 actuation point degrees fahrenheit and -30.00/+10.00 deactuation point degrees fahrenheit

Contact Adjustment Type:

Internal actuation point pointer with scale and internal deactuation point pointer with scale

Contact Stimulus Rating:

90.00 actuation point degrees fahrenheit and -30.00 deactuation point degrees fahrenheit

Contact Voltage Rating In Volts:

240.0 ac at sea level second voltage

Frequency In Hertz:

60.0 second voltage

Media For Which Designed:

Gas

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0