

View Online at <https://aerobasegroup.com/nsn/5930-01-305-3555>

**Mounting Slot Width:**

0.187 inches

**Capillary Tube Length:**

96.0 inches

**Bulb Length:**

5.750 inches

**Bulb Diameter:**

0.375 inches

**End Application:**

Controller/starter used onboard 180 ft wlb coast guard vessels

**Temperature Sensing Element Type:**

Capillary tube-bulb

**Mounting Method:**

Slot

**Cubic Measure:**

5.000 cubic inches

**Contact Action Stimulus:**

Increase

**Nonpile-up Contact Arrangement:**

1 pole, single throw, double make, both positions maintained, with contact on arm

**Terminal Type:**

Screw

**Contact Load Current Rating:**

3.7 amperes motor load second voltage

**Contact Adjustability:**

Actuation point adjustable, preset and deactuation point adjustable, preset

**Contact Adjustment Range:**

+50.00/+90.00 actuation point degrees fahrenheit and -30.00/+10.00 deactuation point degrees fahrenheit

**Contact Adjustment Type:**

Internal actuation point pointer with scale and internal deactuation point pointer with scale

**Contact Stimulus Rating:**

90.00 actuation point degrees fahrenheit and -30.00 deactuation point degrees fahrenheit

**Contact Voltage Rating In Volts:**

240.0 ac at sea level second voltage

**Frequency In Hertz:**

60.0 second voltage

**Media For Which Designed:**

Gas

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A048b0