

View Online at <https://aerobasegroup.com/nsn/5930-01-305-4404>

Thread Class:

2a

Body Style:

Bushing mounted

Hazardous Locations/environmental Protection:

Moisture proof and dustproof

Overall Length:

0.900 inches

Overall Height:

0.562 inches

Overall Width:

0.562 inches

Body Diameter:

0.343 inches

Bushing Length:

Between 0.235 inches and 0.265 inches

Case Material:

Metal

Actuator Diameter:

0.190 inches

Actuator Height:

0.125 inches

Actuator Color:

Black single actuator

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

1 pole, single throw, normally closed, momentary action single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 3.000 amperes inductive dc and 2.000 amperes lamp dc and 5.000 amperes resistive ac and 3.000 amperes inductive ac and 2.000 amperes lamp ac

Thread Series Designator:

Uns

Terminal Type And Quantity:

2 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0