# NSN 5930-01-305-5234

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-305-5234

# Thread Class:

2a single mounting facility

### Thread Length:

0.312 inches single mounting facility

## **Overall Length:**

1.478 inches

#### First Flat Length:

0.250 inches single actuator

#### Flat Height:

0.094 inches single actuator

#### Shaft Diameter:

0.125 inches single actuator

#### Shaft Length:

0.375 inches single actuator

#### **Overall Diameter:**

0.687 inches

#### Individual Section Quantity:

1

# Nonturn Device Type:

Flatted bushing at 3: 00 o'clock

### Switch Contact Basic Design:

Nonpile-up symmetrical

### Pole Quantity:

1 single section front

### Throw Quantity:

10 single section rear

### **Mounting Method:**

Threaded bushing single mounting facility

### Thread Size:

0.250 inches single mounting facility

### Contact Voltage Rating In Volts:

28.0 dc at sea level

### **Rotor Through Connection Quantity:**

1 single section

### Switch Actuator Indexing Position Quantity:

10 single actuator

### Shaft Type:

Round, flatted single actuator

## **Terminal Type:**

Printed circuit

### **Contact Switching Action:**

Breaks before makes single section rear

# NSN 5930-01-305-5234

Rotary Switch - Page 2 of 2



#### Switch Actuator Positioning Increment:

30.0 degrees single actuator

#### Switch Actuator Stop Device Type:

Fixed stop single actuator

#### **Contact Load Current Rating:**

500.0 milliamperes resistive load dc at sea level and 250.0 milliamperes inductive load dc at sea level

#### Style Designator:

Tap, circular, bushing mount

#### **Test Data Document:**

81349-mil-s-3786 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator: Unef single mounting facility

# Specification Data:

81349-mil-s-3786/39 government specification

Shelf Life:

N/a

---

Unit Of Measure:

Demilitarization:

No

Fiig:

A052b0