

View Online at <https://aerobasegroup.com/nsn/5930-01-305-5235>

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

0.620 inches

Overall Height:

1.405 inches

Overall Width:

0.320 inches

Bushing Length:

0.350 inches

Body Length:

0.500 inches

Body Width:

0.270 inches

Body Height:

0.350 inches

Case Material:

Plastic

Actuator Style:

Round

Actuator Diameter:

0.115 inches

Actuator Height:

0.410 inches

Actuator Position-action Relationship:

Up position momentary and down position momentary and center position maintained

Maximum Voltage Rating In Volts:

250.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Nonpile-up Contact Arrangement:

1 pole, double throw, two positions momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 2.000 amperes resistive ac

Special Features:

Unthreaded bushing; bracket with printed circuit board mounting pins provided

Precious Material And Location:

Contact and terminal surfaces silver

Terminal Type And Quantity:

3 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0