

View Online at <https://aerobasegroup.com/nsn/5930-01-305-5238>

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Corrosion resistant and moisture resistant and vibration resistant

Overall Length:

0.620 inches

Overall Height:

1.544 inches

Overall Width:

0.450 inches

Bushing Length:

0.280 inches

Body Length:

0.500 inches

Body Width:

0.450 inches

Body Height:

0.410 inches

Actuator Style:

Rectangular

Actuator Height:

0.450 inches

Actuator Width:

0.100 inches

Actuator Position-action Relationship:

Up position maintained and down position momentary

Maximum Voltage Rating In Volts:

20.0 ac and 20.0 dc

End Application:

Transmitting set, radio an/frt-96

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

20.000 milliamperes resistive dc and 20.000 milliamperes resistive ac

Special Features:

Unthreaded bushing; bracket with printed circuit board mounting pins provided

Precious Material And Location:

Contact and terminal surfaces gold

Terminal Type And Quantity:

6 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0