

View Online at <https://aerobasegroup.com/nsn/5930-01-305-5238>

**Body Style:**

Bushing mount

**Hazardous Locations/environmental Protection:**

Corrosion resistant and moisture resistant and vibration resistant

**Overall Length:**

0.620 inches

**Overall Height:**

1.544 inches

**Overall Width:**

0.450 inches

**Bushing Length:**

0.280 inches

**Body Length:**

0.500 inches

**Body Width:**

0.450 inches

**Body Height:**

0.410 inches

**Actuator Style:**

Rectangular

**Actuator Height:**

0.450 inches

**Actuator Width:**

0.100 inches

**Actuator Position-action Relationship:**

Up position maintained and down position momentary

**Maximum Voltage Rating In Volts:**

20.0 ac and 20.0 dc

**End Application:**

Transmitting set, radio an/frt-96

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Nonpile-up Contact Arrangement:**

2 pole, double throw, one position momentary single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

20.000 milliamperes resistive dc and 20.000 milliamperes resistive ac

**Special Features:**

Unthreaded bushing; bracket with printed circuit board mounting pins provided

**Precious Material And Location:**

Contact and terminal surfaces gold

**Terminal Type And Quantity:**

6 printed circuit

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0