

View Online at <https://aerobasegroup.com/nsn/5930-01-305-5240>

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

0.850 inches

Overall Height:

1.568 inches

Overall Width:

0.500 inches

Bushing Length:

0.312 inches

Body Length:

0.850 inches

Body Width:

0.500 inches

Body Height:

0.475 inches

Case Material:

Plastic

Actuator Style:

Round

Actuator Diameter:

0.214 inches

Actuator Height:

0.610 inches

Actuator Position-action Relationship:

Up position maintained and down position maintained

Actuator Position-locking Relationship:

Up position locked in and down position locked in

Maximum Voltage Rating In Volts:

120.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

40

Thread Size:

0.250 inches

Nonpile-up Contact Arrangement:

4 pole, double throw, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 5.000 amperes resistive ac

Precious Material And Location:

Contact and terminal surfaces silver

Thread Series Designator:

Uns

Terminal Type And Quantity:

12 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0