## NSN 5930-01-305-6246

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-305-6246

Body Style:
Hole mounted
Hazardous Locations/environmental Protection:
Watertight
Overall Length:
17.625 inches
Overall Height:
2.094 inches
Overall Width:
2.250 inches
Actuator Style:
Flexible
Actuator Diameter:
0.125 inches
Housing Height:
2.094 inches
Housing Width:
2.250 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Height:
1.500 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Length:
4.125 inches
Maximum Voltage Rating In Volts:
600.0 ac and 600.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Nonpile-up Contact Arrangement:
1 two circuit, double break/double make, one position momentary single switch unit
Switch Actuating Force:
72.0 inch-ounces
Actuator Movement:
9.0 pretravel degrees and 1.0 overtravel degrees and 4.0 differential degrees
Contact Load Current Rating At Maximum Rated Voltage:
0.200 amperes resistive dc and 1.200 amperes resistive ac
Terminal Type And Quantity:
4 screw
Shelf Life:
N/a
Unit Of Measure:

--

## NSN 5930-01-305-6246

Sensitive Switch - Page 2 of 2



Demilitarization:

No

Fiig:

A053a0