

View Online at <https://aerobasegroup.com/nsn/5930-01-305-7199>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.275 inches single mounting facility

**Overall Length:**

1.455 inches

**Flat Height:**

0.217 inches single actuator

**Shaft Diameter:**

0.250 inches single actuator

**Shaft Length:**

0.320 inches single actuator

**Overall Diameter:**

1.031 inches

**Individual Section Quantity:**

1

**Nonturn Device Type:**

Flatted bushing at 3: 00 o'clock

**Operating Temperature Range:**

-30.0/+85.0 degrees celsius

**End Application:**

6625-01-278-8010 divider, power, radio frequency

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

3 single section rear

**Throw Quantity:**

4 single section rear

**Mounting Method:**

Threaded bushing single mounting facility

**Thread Size:**

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:**

250.0 dc at sea level

**Switch Actuator Indexing Position Quantity:**

4 single actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Breaks before makes single section rear

**Switch Actuator Positioning Increment:**

30.0 degrees single actuator

**Contact Load Current Rating:**

150.0 milliamperes resistive load dc at sea level

**Precious Material And Location:**

Contact and terminal surfaces silver

**Precious Material:**

Silver

**Style Designator:**

Tap, circular, bushing mount

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A052b0