NSN 5930-01-305-8625

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-305-8625

View Online at https://aerobasegroup.com/nsn/5930-01-305-8625
Hazardous Locations/environmental Protection:
Corrosion resistant
Overall Length:
5.750 inches
Overall Height:
3.000 inches
Overall Width:
2.810 inches
Unthreaded Mounting Hole Diameter:
0.201 inches single mounting facility
Individual Section Quantity:
3
Knob Manufacturer Code:
82121
Knob Manufacturer Part Number:
02000-12
Longest Horizontal Distance Between Mounting Centers:
2.000 inches single mounting facility
Shortest Horizontal Distance Between Mounting Centers:
1.000 inches single mounting facility
Longest Vertical Distance Between Mounting Centers:
2.188 inches single mounting facility
Switch Contact Basic Design:
Nonpile-up nonsymmetrical
Mounting Method:
Bracket single mounting facility and unthreaded hole single mounting facility
Features Provided:
Actuator knob and legend plate
Contact Voltage Rating In Volts:
600.0 highest ac voltage rating at sea level
Switch Actuator Momentary Position:
Clockwise single actuator
Mounting Facility Pattern:
Isosceles triangle single mounting facility
Switch Actuator Indexing Position Quantity:
4 single actuator
Terminal Type:
Screw
Contact Switching Action:
Breaks before makes each section periphery

45.0 degrees single actuator

Switch Actuator Positioning Increment:

NSN 5930-01-305-8625

Rotary Switch - Page 2 of 2

Fiig: A052b0



Switch Actuator Stop Device Type: Adjustable stop single actuator **Contact Load Current Rating:** 6.0 amperes resistive load highest ac voltage rating at sea level **Special Features:** Legend plate reads ckt bkr cont trip close **Precious Material And Location:** Contact surfaces silver **Precious Material:** Silver Style Designator: Tap, circuit selector Shelf Life: N/a **Unit Of Measure:** Demilitarization: No