Code Indicating Wheel Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-305-9310

Hazardous Locations/environmental Protection:
Shock resistant and vibration resistant
Overall Length:
4.800 inches
Overall Height:
1.791 inches
Overall Width:
1.156 inches
Unthreaded Mounting Hole Diameter:
0.100 inches single mounting facility
Individual Section Quantity:
8
Longest Horizontal Distance Between Mounting Centers:
4.630 inches single mounting facility
Longest Vertical Distance Between Mounting Centers:
0.900 inches single mounting facility
End Application:
Receiving set, sonar an/bqr-15
Mounting Method:
Bracket single mounting facility and unthreaded hole single mounting facility
Actuator Type:
Thumbwheel all actuators
Contact Voltage Rating In Volts:
28.0 dc at sea level
Mounting Facility Pattern:
Four position rectangular single mounting facility
Switch Actuator Indexing Position Quantity:
2 all actuators
Terminal Type:
Printed circuit
Contact Load Current Rating:
125.0 milliamperes resistive load dc at sea level
Readout Indicator Marking:
0, 1 each section
Contact Arrangement Truth Table:
Special each section
Special Truth Table Identification:
01963-special 1-2 each section
Color:
White each indicator marking
Precious Material And Location:
Contact and printed circuit board circuit surfaces gold and contacts silver

AeroBase Group

## **Precious Material:**

Gold and silver

## Style Designator:

Rectangular inline indicating

Shelf Life:

N/a

## Unit Of Measure:

---

## Demilitarization:

No

Fiig:

A052b0