## NSN 5930-01-306-0830

Slide Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-306-0830
Body Style:
Hole mounted
Overall Length:
1.000 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
0.812 inches
Overall Height:
0.514 inches
Overall Width:
0.404 inches
Body Length:
0.740 inches
Body Width:
0.404 inches
Body Height:
0.295 inches
Unthreaded Mounting Hole Diameter:
0.100 inches
Actuator Length:
0.218 inches
Actuator Height:
0.453 inches
Actuator Width:
0.125 inches

## **Actuator Position-action Relationship:**

Left position maintained and right position maintained

#### **Actuator Color:**

Black single actuator

### Maximum Voltage Rating In Volts:

125.0 ac and 125.0 dc

#### **Mounting Method:**

Unthreaded hole

#### **Nonpile-up Contact Arrangement:**

2 pole, double throw, both positions maintained single switch unit

#### **Contact Load Current Rating At Maximum Rated Voltage:**

0.500 amperes resistive dc and 0.500 amperes resistive ac

#### **Special Features:**

Side actuated

#### **Precious Material And Location:**

Contact and terminal surfaces silver

#### **Terminal Type And Quantity:**

6 printed circuit

# NSN 5930-01-306-0830

Slide Switch - Page 2 of 2



_			-		
C	hΔ	Iŧ.		ife:	
•			_	IIC.	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A053a0