## NSN 5930-01-306-2408

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-306-2408

View Online at https://aerobasegroup.com/nsn/5930-01-306-2408
Overall Length:
2.719 inches
Outside Diameter:
0.125 inches single connection
Body Length:
1.750 inches
Overall Diameter:
1.125 inches
Pressure Switch Type:
Gage
Operating Tempurature Rating:
Between -65.0 degrees fahrenheit and 225.0 degrees fahrenheit
Mounting Method:
Inlet connection
Contact Action Stimulus:
Increase
Proof Pressure:
5000.00 pounds per square inch gage
Thread Size:
0.125 inches single pressure connection
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary
Terminal Type:
Tab w/screw
Contact Load Current Rating:
5.0 amperes resistive load second voltage and 3.0 amperes inductive load second voltage
Contact Adjustability:
Actuation point adjustable
Contact Adjustment Range:
+3.00/+100.00 actuation point pounds per square inch gage and +1.20/+91.00 deactuation point pounds per square inch gage
Contact Adjustment Type:
External actuation point lock ring and external deactuation point lock ring
Contact Voltage Rating In Volts:
28.0 dc at sea level second voltage
Pressure Connector Type:
Plain, threaded external single connection
Special Features:
Cage 60233 complete p/n is j205g-10s-k51ts-n.O60p.S.I.G-decrease. This item is in their catalog
Media For Which Designed:
Gas or liquid

Cylindrical

Style Designator:

## NSN 5930-01-306-2408

Pressure Switch - Page 2 of 2



T	<b>h</b> r	ead	<b>Series</b>	Design	nator:

Npt single pressure connection

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A048b0