## NSN 5930-01-306-2408

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-306-2408

## **Overall Length:**

2.719 inches

## **Outside Diameter:**

0.125 inches single connection

## **Body Length:**

1.750 inches

## **Overall Diameter:**

1.125 inches

#### Pressure Switch Type:

Gage

## **Operating Tempurature Rating:**

Between -65.0 degrees fahrenheit and 225.0 degrees fahrenheit

## **Mounting Method:**

Inlet connection

## **Contact Action Stimulus:**

Increase

## Proof Pressure:

5000.00 pounds per square inch gage

## Thread Size:

0.125 inches single pressure connection

## Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

## Terminal Type:

Tab w/screw

## **Contact Load Current Rating:**

5.0 amperes resistive load second voltage and 3.0 amperes inductive load second voltage

## **Contact Adjustability:**

Actuation point adjustable

## **Contact Adjustment Range:**

+3.00/+100.00 actuation point pounds per square inch gage and +1.20/+91.00 deactuation point pounds per square inch gage

## **Contact Adjustment Type:**

External actuation point lock ring and external deactuation point lock ring

## **Contact Voltage Rating In Volts:**

28.0 dc at sea level second voltage

## Pressure Connector Type:

Plain, threaded external single connection

## **Special Features:**

Cage 60233 complete p/n is j205g-10s-k51ts-n.O.-60p.S.I.G-decrease. This item is in their catalog

## Media For Which Designed:

Gas or liquid

## Style Designator:

Cylindrical

# NSN 5930-01-306-2408

Pressure Switch - Page 2 of 2



**Thread Series Designator:** 

Npt single pressure connection

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A048b0