NSN 5930-01-306-5178

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-306-5178

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Corrosion resistant

Overall Length:

2.500 inches

Overall Height:

1.500 inches

Overall Width:

1.625 inches

Case Material:

Metal

Housing Height:

1.500 inches

Housing Length:

2.250 inches

Housing Width:

1.625 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Height:

1.156 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Length:

1.812 inches

Maximum Voltage Rating In Volts:

600.0 ac

Inclosure Type:

Fully enclosed

Nonpile-up Contact Arrangement:

3 two circuit, both positions maintained single switch unit

Switch Actuating Force:

48.0 inch-ounces

Actuator Movement:

15.0 pretravel degrees and 75.0 overtravel degrees and 6.0 differential degrees

Contact Load Current Rating At Maximum Rated Voltage:

1.200 amperes resistive ac

Special Features:

Less actuator; eight foot long cable

Precious Material And Location:

Contacts silver

Terminal Type And Quantity:

12 wire lead

Shelf Life:

N/a

NSN 5930-01-306-5178

Sensitive Switch - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0

