NSN 5930-01-306-8805

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-306-8805

Body Style:
Hole mounted
Hazardous Locations/environmental Protection:
Fungus proof and moisture proof
·
Overall Length: 5.312 inches
Overall Height: 2.562 inches
Overall Width:
2.625 inches
Actuator Style:
Round
Housing Height:
2.562 inches
Housing Length:
5.312 inches
Housing Width:
2.250 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Length:
4.219 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Width:
1.812 inches
Maximum Voltage Rating In Volts:
440.0 ac and 230.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Nonpile-up Contact Arrangement:
1 two circuit, double break/double make, one position momentary single switch unit
Actuator Movement:
16.0 pretravel degrees
Contact Load Current Rating At Maximum Rated Voltage:
5.000 amperes resistive dc and 5.000 amperes resistive ac
Terminal Type And Quantity:
4 screw
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

NSN 5930-01-306-8805 Sensitive Switch - Page 2 of 2



Fiig:

A053a0