NSN 5930-01-306-8806

Slide Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-306-8806

Body Style:
Hole mounted
Overall Length:
1.615 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.338 inches
Overall Height:
0.893 inches
Overall Width:
0.650 inches
Body Length:
1.030 inches
Body Width:
0.650 inches
Body Height:
0.625 inches
Unthreaded Mounting Hole Diameter:
0.130 inches
Actuator Length:
0.175 inches
Actuator Width:
0.315 inches
Actuator Position-action Relationship:
Left position maintained and right position maintained
Maximum Voltage Rating In Volts:
250.0 ac
End Application:
4935-01-142-3733 test position, shock equipment
Mounting Method:
Unthreaded hole
Nonpile-up Contact Arrangement:
2 pole, double throw, both positions maintained single switch unit
Contact Load Current Rating At Maximum Rated Voltage:
5.000 amperes resistive ac
Special Features:
Actuator is flush with body
Terminal Type And Quantity:
6 tab, solder lug
Shelf Life:
N/a
Unit Of Measure

--

NSN 5930-01-306-8806

Slide Switch - Page 2 of 2



_		••	• •				
וו	em	ш	112	rız	211	n	٠.

No

Fiig:

A053a0