NSN 5930-01-306-8816

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-306-8816

| Body Style: |
|--|
| Panel mount |
| Hazardous Locations/environmental Protection: |
| Explosion proof and moisture resistant and salt spray resistant |
| Overall Length: |
| 0.740 inches |
| Overall Height: |
| 3.060 inches |
| Overall Width: |
| 0.740 inches |
| Body Length: |
| 0.740 inches |
| Body Width: |
| 0.740 inches |
| Case Material: |
| Metal |
| Actuator Length: |
| 0.740 inches |
| Actuator Style: |
| Rectangular |
| Actuator Width: |
| 0.740 inches |
| Actuator Color: |
| White single actuator and white single actuator |
| Maximum Voltage Rating In Volts: |
| 115.0 ac and 28.0 dc |
| End Application: |
| Sonar set an/bqq-6 |
| Inclosure Type: |
| Fully enclosed |
| Mounting Method: |
| Panel |
| Nonpile-up Contact Arrangement: |
| 2 pole, double throw, one position momentary single switch unit |
| Contact Load Current Rating At Maximum Rated Voltage: |
| 5.000 amperes resistive dc and 2.500 amperes inductive dc and 1.500 amperes lamp dc and 5.000 amperes resistive ac and 2.500 amperes |
| inductive ac and 1.500 amperes lamp ac |
| Special Features: |
| Lamp terminals provided; horizontal split lens |
| Precious Material And Location: |
| |

Unable to decode and unable to decode

Unable To Decode:

Contact surfaces gold and contacts silver

NSN 5930-01-306-8816

Push Switch - Page 2 of 2



11 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0