

View Online at <https://aerobasegroup.com/nsn/5930-01-307-3360>

Hazardous Locations/environmental Protection:

Dripproof

Overall Length:

8.000 inches

Overall Height:

9.500 inches

Unthreaded Mounting Hole Diameter:

0.281 inches single mounting facility

Individual Section Quantity:

4

Longest Horizontal Distance Between Mounting Centers:

4.000 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

8.750 inches single mounting facility

Switch Contact Basic Design:

Nonpile-up symmetrical

Mounting Method:

Bracket single mounting facility and unthreaded hole single mounting facility

Features Provided:

Actuator knob and legend plate and cam actuated and metallic inclosure

Contact Voltage Rating In Volts:

600.0 highest dc voltage rating at sea level

Mounting Facility Pattern:

Four position rectangular single mounting facility

Cam Actuated Switch Contact Arrangement:

1 pole, single throw, double make, both positions maintained each switch each section in-line

Switch Actuator Indexing Position Quantity:

2 single actuator

Terminal Type:

Screw

Contact Load Current Rating:

6.0 amperes resistive load lowest ac voltage rating at sea level

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0