## NSN 5930-01-307-3392

Rotary Switch - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5930-01-307-3392

| Hazardous Locations/environmental Protection:                                |
|--|
| Dripproof  |
| Overall Length:  |
| 4.375 inches   |
| Overall Height:  |
| 4.500 inches   |
| Overall Width:   |
| 3.500 inches   |
| Unthreaded Mounting Hole Diameter:   |
| 0.219 inches single mounting facility  |
| Longest Horizontal Distance Between Mounting Centers:                        |
| 2.375 inches single mounting facility  |
| Longest Vertical Distance Between Mounting Centers:                          |
| 4.000 inches single mounting facility  |
| Mounting Method:   |
| Flange single mounting facility and unthreaded hole single mounting facility |
| Features Provided:   |
| Actuator knob and metallic inclosure   |
| Contact Voltage Rating In Volts:   |
| 600.0 highest dc voltage rating at sea level                                 |
| Mounting Facility Pattern:   |
| Four position rectangular single mounting facility                           |
| Switch Actuator Indexing Position Quantity:                                  |
| 3 single actuator  |
| Terminal Type:   |
| Tab w/screw  |
| Contact Load Current Rating:   |
| 6.0 amperes resistive load lowest ac voltage rating at sea level             |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| No   |
| Fiig:  |
| A052b0   |
|  |